

**36W LED Light Power Supply**

**产品优势**

- 隔离式恒流电性设计
- 快速启动
- 输入全球电压范围： 85~264Vac
- 过流过压短路等多重保护方式
- 高功率因素:>0.98@115Vac;>0.96@230Vac@full load
- 高效率:>85% at max load, 220Vac/60Hz, 25°C.
- 小巧尺寸: Ø85x30mm
- 高可靠性
- 2年质量保证

**电性参数规格表 @25°C**

型号.		TLP36-S24-03C3	TLP36-S36-03C3
输入	输入电压范围	AC90V~264V	
	频率	47Hz ~63 Hz	
	电流	0.75A (RMS) max for 110Vac at max load 0.25A (RMS) max for 220Vac at max load	
输出	标准电压	24Vdc	36Vdc
	适用范围	18~24Vdc	24~38Vdc
	额定电流	1.5A	1A
	额定功率	<b>36W</b>	
	功率因素	>0.96 at full load 110Vac or 220Vac.	
	转换效率	>85% at max load, 220Vac/60Hz, 25°C.	
	启动时间	<500mS	
	保护设计	Over Voltage/Over Current/Short Circuit Protection	
环境要求	储存温度	-40~80 °C	
	工作温度	-25~45 °C	
安规及电磁兼容	安全标准	EN61347-2-13 UL1310(Pending)	
	EMI (Conducted & Radiation)	Compliance to EN55015;EN55022 Class 2	
	EMS immunity	EN6100-3-2; EN61547; light industry level, criteria A	
	国际认证	CE	
其他参数	外尺寸(mm) L*W*H	Ø85x30mm	
	包装	0.26kg; 100pcs/26kg;0.51cuft	
Note	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25 of ambient temperature. 2. Tolerance : includes set up tolerance, line regulation and load regulation. 3. Derating may be needed under low input voltage. Please check the derating curve for more details. 4. The power supply is For LED Light Use Only.		